

## Ameren Illinois Utilities List of Available Energy Efficient Measures

As of September, 2009. Subject to change. See ActOnEnergy.com for current program details.

### Residential

<u>Program</u>	<u>Measure</u>
<b>Appliance Recycling</b>	Refrigerator/Freezer Recycling
<b>Res New HVAC</b>	Ground Source Heat Pump Size AC Units to 100% of Manual J Energy Star CAC (14 SEER) Energy Star ER CAC (14 SEER) 92% Efficient Furnace 95% Efficient Furnace
<b>Low Income Gas</b>	No Furnace With Furnace
<b>Lighting &amp; Appliance</b>	Energy Star Ceiling Fan Energy Star De-humidifier Energy Star Window AC
<b>Res New Construction</b>	Energy Star Home - gas only Energy Star Home- dual fuel
<b>Home Energy Performance-Electric</b>	R-11 Wall Insulation Infiltration from .8 to .35 ACH Faucet Aerators (Existing) Low Flow Shower Heads (Existing) Hot Water pipe Insulation (Existing) Hot Water Insulation (Existing) Ceiling Insulation (R-7 to R-39) Ceiling Insulation (R-11 to R-38) CFL 60W to 15W CFL 75W to 20W CFL 100W to 23W
<b>Home Energy Performance-Gas</b>	Ceiling insulation (R-38) Duct leakage 5% Faucet Aerators Hot Water Insulation (Existing) Hot Water Pipe Insulation Increase duct sizes or add new ducts Infiltration=.35 ACH Low Flow Shower Heads (Existing)

**Multi-Family  
Electric**

Low-e Double Pane Windows  
Programmable Thermostat  
R-11 Wall Insulation  
  
Central AC (Correct Charge, Test Only)  
Central AC (Correct Charge from undercharged condition)  
Central AC (Correct Charge from overcharged condition)  
Common Area Integral CFL, screw-in, 40w to 13w  
Common Area Integral CFL, screw-in, 60w to 15w  
Common Area Integral CFL, screw-in, 75w to 18w  
In-unit Integral CFL 60w to 15w  
In-unit Integral CFL 75w to 20w  
In-unit Integral CFL 100w to 23w  
Modular CFL, pin based, 100w to 23w  
2 4' T8 32 watt lamps with EB  
LED Exit Sign (retrofit kit)  
DHW wrap R-4  
Pipe Insulation  
Faucet Aerators  
Low Flow Shower Heads

**Multi-Family Gas**

90% Efficient Commercial Furnace  
Faucet Aerators  
Hot Water Pipe Insulation  
Showerhead  
Infiltration = 0.35 ACH  
MF Efficient Boiler  
Programmable Thermostat  
R-11 Wall Insulation