(1) E-1400 SETUP PARAMETERS

FUNCTION	CH. 1	CH. 2	CH. 3	CH. 4
FREQUENCY SETTING	2	4	6	8
SENSITIVIY SETTING	6•	6•	6•	6•
OPTION 1 (TEMP L DISPLAY)	OFF			
OPTION 2 (TEMP ΔL/L DISPLAY)	OFF			
OPTION 3 (NOISE FILTER)	3.00	3.00	3.00	3.00
OPTION 4 (TRACKING)	4.02	4.02	4.02	4.02
OPTION 5 (SENSITIVITY BOOST)	5.00	5.00	5.00	5.00
OPTION 6 (TEMP AUDIBLE SIGNAL)	OFF	OFF	OFF	OFF
CHECKLOOP INTERVAL	005	005	005	005
DETECTOR ID	000			
OPTION 7 (DETECTOR SYNC)	7.01			
OPTION 8 (ISL OPTION)	OFF			
OPTION 9 (SHUNT ENHANCEMENT SE)	OFF	OFF	OFF	OFF
MAIN VITAL OUTPUT DELAY	00.0	00.0	00.0	00.0
MAIN VITAL OUTPUT EXTENSION	00.0	00.0	00.0	00.0
MAIN VITAL OUTPUT MAPPING	10	20	40	80
AUX VITAL OUTPUT MAPPING	001	002	004	008
LOOP FREQUENCY (Khz)				
LOOP INDUCTANCE (MICRO HENRIES)				

SOFTWARE VERSION 4.02
• FIELD VERIFY

(2) E-1400 SETUP PARAMETERS

FUNCTION	CH. 1	CH. 2	CH. 3	CH. 4
FREQUENCY SETTING	2	4	6	8
SENSITIVIY SETTING	6•	6•	OFF•	OFF•
OPTION 1 (TEMP L DISPLAY)	OFF			
OPTION 2 (TEMP ΔL/L DISPLAY)	OFF			
OPTION 3 (NOISE FILTER)	3.00	3.00	3.00	3.00
OPTION 4 (TRACKING)	4.02	4.02	4.02	4.02
OPTION 5 (SENSITIVITY BOOST)	5.00	5.00	5.00	5.00
OPTION 6 (TEMP AUDIBLE SIGNAL)	OFF	OFF	OFF	OFF
CHECKLOOP INTERVAL	005	005	005	005
DETECTOR ID	001			
OPTION 7 (DETECTOR SYNC)	7.01			
OPTION 8 (ISL OPTION)	OFF			
OPTION 9 (SHUNT ENHANCEMENT SE)	OFF	OFF	OFF	OFF
MAIN VITAL OUTPUT DELAY	00.0	00.0	00.0	00.0
MAIN VITAL OUTPUT EXTENSION	00.0	00.0	00.0	00.0
MAIN VITAL OUTPUT MAPPING	10	20	40	80
AUX VITAL OUTPUT MAPPING	001	002	004	008
LOOP FREQUENCY (Khz)				
LOOP INDUCTANCE (MICRO HENRIES)				

SOFTWARE VERSION 4.02
• FIELD VERIFY



CABLE TABULATION

CABLE NO. (17) 6/PR #18 U.G.C. TO JCT BOX ON BASE OF GATE "A" (RCL PART #03-094-005)
CABLE NO. (18) 6/PR #18 U.G.C. TO JCT BOX ON BASE OF GATE "B" (RCL PART #03-094-005)
CABLE NO. (19) 6/PR #18 U.G.C. TO JCT BOX ON BASE OF GATE "C" (RCL PART #03-094-005)
CABLE NO. (20) 6/PR #18 U.G.C. TO JCT BOX ON BASE OF GATE "D" (RCL PART #03-094-005)

NEW SHEET

Designed: 12/12/13
TIER 4 ILLINOIS HIGH SPEED RAIL PROJECT
PHASE 3
MP 118.25-124.85
Rec*: WO*: 22817
ISL: /NBT
/WIT/RLL

MODIFICATION LEVEL	
O. A. LAST LEVEL CHECKED	DU
LAST LEVEL MOD THIS TYPICAL	DU
LAST LEVEL BY DESIGNER	DU
CHANGED FROM TYPICAL?	Y

Rev 01.24.11 4K 2TKEGMS.9

CIRCUIT MODIFICATIONS ARE NOT TO BE MADE WITHOUT AUTHORITY FROM THE OFFICE OF SIGNAL DESIGN

DATE: 12/12/13
DES: WIT CHK: NBT
PID: 85679
WO: 22817

UNION PACIFIC RAILROAD
NORMAL, ILLINOIS
BROADWAY
JOLIET SUBDIVISION
Office of AVP Engineering - Signal Omaha, Nebraska

SH. 9
DOT 290812D
M.P. 124.20
ID=CSL12420.9X





NEW SHEET

Designed: 12/12/13
TIER 4 ILLINOIS HIGH SPEED RAIL PROJECT
PHASE 3
MP 118.25-124.85
Rec#: WO#: 22817
IS: /NBT
/ /WIT/RLL

MODIFICATION LEVEL	
O. A. LAST LEVEL CHECKED	DU
LAST LEVEL MOD THIS TYPICAL	DU
LAST LEVEL BY DESIGNER	DU
CHANGED FROM TYPICAL?	Y

REV 01.24.11 4K 2TKEGMS.9B

CIRCUIT MODIFICATIONS ARE NOT TO BE MADE WITHOUT AUTHORITY FROM THE OFFICE OF SIGNAL DESIGN

DATE: 12/12/13
DES: WIT CHK: NBT
PID: 85679
WO: 22817

UNION PACIFIC RAILROAD
NORMAL, ILLINOIS
BROADWAY
JOLIET SUBDIVISION
Office of AVP Engineering - Signal Omaha, Nebraska

SH. 9A
DOT 290812D
M.P. 124.20
ID=CSL12420.9AX





NOTES

1. TB1 PROVIDES AN EXTERNAL PASS THROUGH BETWEEN THE E-1400 MODULES AND THE VITAL INPUT MODULE IN CHASSIS POSITION 6. EGMS OR EGMS+ UNITS CONFIGURED FOR LESS THAN 4 EACH E-1400 MODULES WILL ONLY BE WIRED AS REQUIRED.
2. TB2-3 THROUGH TB2-8 PROVIDE A CONNECTION BUS FOR INTERNAL SUPPLY VOLTAGES AND MUST NOT BE USED TO SUPPLY OTHER CIRCUITS.

NEW SHEET

Designed: 12/12/13
TIER 4 ILLINOIS HIGH SPEED RAIL PROJECT
PHASE 3
MP 118.25-124.85
Rec#: WO#: 22817
IS: /NBT
/ /WIT/RLL

MODIFICATION LEVEL	
O. A. LAST LEVEL CHECKED	DU
LAST LEVEL MOD THIS TYPICAL	DU
LAST LEVEL BY DESIGNER	DU
CHANGED FROM TYPICAL?	Y

REV 01.24.11 4K 2TKEGMS.9C

CIRCUIT MODIFICATIONS ARE NOT TO BE MADE WITHOUT AUTHORITY FROM THE OFFICE OF SIGNAL DESIGN

DATE: 12/12/13
DES: WIT CHK: NBT
PID: 85679
WO: 22817

UNION PACIFIC RAILROAD
NORMAL, ILLINOIS
BROADWAY
JOLIET SUBDIVISION
Office of AVP Engineering - Signal Omaha, Nebraska

SH. 9B
DOT 290812D
M.P. 124.20
ID=CSL12420.9BX



NEW SHEET

					Designed: 12/12/13 TIER 4 ILLINOIS HIGH SPEED RAIL PROJECT PHASE 3 MP 118.25-124.85 Rec'd: WO#: 22817 ISs: /NBT / /WIT/RLL	MODIFICATION LEVEL O. A. LAST LEVEL CHECKED DU LAST LEVEL MOD THIS TYPICAL DU LAST LEVEL BY DESIGNER DU CHANGED FROM TYPICAL? Y Rev 01.24.11 4K 2TKEGMS.9D	CIRCUIT MODIFICATIONS ARE NOT TO BE MADE WITHOUT AUTHORITY FROM THE OFFICE OF SIGNAL DESIGN	DATE: 12/12/13 DES: WIT CHK: NBT PID: 85679 WO: 22817	UNION PACIFIC RAILROAD NORMAL, ILLINOIS BROADWAY JOLIET SUBDIVISION Office of AVP Engineering - Signal Omaha, Nebraska	SH. 9C DOT 290812D M.P. 124.20 ID=CSL12420.9CX



NOTES:

1. INPUT WIRES, OUTPUT WIRES, POWER WIRES, PUT IN SEPARATE BUNDLES.
2. ALL WIRES #16 UNLESS NOTED.
3. O??O 2 POSITION WAGO BLOCK.

NEW SHEET

Designed: 12/12/13
TIER 4 ILLINOIS HIGH SPEED RAIL PROJECT
PHASE 3
MP 118.25-124.85
Rec#: WO#: 22817
IS: / /NBT / /WIT/RLL

CIRCUIT MODIFICATIONS ARE NOT TO BE MADE WITHOUT AUTHORITY FROM THE OFFICE OF SIGNAL DESIGN

DATE: 12/12/13	
DES: WIT CHK: NBT	
PID: 85679	
WO: 22817	

UNION PACIFIC RAILROAD
NORMAL, ILLINOIS
BROADWAY
JOLIET SUBDIVISION
Office of AVP Engineering - Signal Omaha, Nebraska

SH.	10
DOT	290812D
M.P.	124.20
ID=CSL12420.10X	



NEW SHEET

Designed: 12/12/13
TIER 4 ILLINOIS HIGH SPEED RAIL PROJECT
PHASE 3
MP 118.25-124.85
Rec*: WO*: 22817
IS: /NBT
/ / WIT/RLL

CIRCUIT MODIFICATIONS ARE NOT TO BE MADE WITHOUT AUTHORITY FROM THE OFFICE OF SIGNAL DESIGN

DATE: 12/12/13
DES: WIT CHK: NBT
PID: 85679
WO: 22817

UNION PACIFIC RAILROAD

NORMAL, ILLINOIS
BROADWAY
JOLIET SUBDIVISION

Office of AVP Engineering - Signal Omaha, Nebraska

SH. 10A
DOT 290812D
M.P. 124.20
ID=CSL12420.10AX



NEW SHEET

Designed: 12/12/13
TIER 4 ILLINOIS HIGH SPEED RAIL PROJECT PHASE 3
MP 118.25-124.85
Rec#: IS: / / WO#: 22817 /NBT / WIT/RLL

CIRCUIT MODIFICATIONS ARE NOT TO BE MADE WITHOUT AUTHORITY FROM THE OFFICE OF SIGNAL DESIGN

DATE: 12/12/13	
DES: WIT	CHK: NBT
PID: 85679	
WO: 22817	

UNION PACIFIC RAILROAD

NORMAL, ILLINOIS
BROADWAY
JOLIET SUBDIVISION

Office of AVP Engineering - Signal Omaha, Nebraska

SH.	10B
DOT	290812D
M.P.	124.20
ID=CSL12420.10BX	





ELECTROLOGIXS WAGO BLOCKS

NEW SHEET

Designed: 12/12/13
TIER 4 ILLINOIS HIGH SPEED RAIL PROJECT
PHASE 3
MP 118.25-124.85
Rec*: WO*: 22817
IS: / /NBT
/ /WIT/RLL

CIRCUIT MODIFICATIONS ARE NOT TO BE MADE WITHOUT AUTHORITY FROM THE OFFICE OF SIGNAL DESIGN

DATE: 12/12/13
DES: WIT CHK: NBT
PID: 85679
WO: 22817

UNION PACIFIC RAILROAD
NORMAL, ILLINOIS
BROADWAY
JOLIET SUBDIVISION
Office of AVP Engineering - Signal Omaha, Nebraska

SH. 10C
DOT 290812D
M.P. 124.20
ID=CSL12420.10CX



NEW SHEET

Designed: 12/12/13
TIER 4 ILLINOIS HIGH SPEED RAIL PROJECT
PHASE 3
MP 118.25-124.85
Rec*: WO*: 22817
By: /NBT
/ /WIT/RLL

CIRCUIT MODIFICATIONS ARE NOT TO BE MADE WITHOUT AUTHORITY FROM THE OFFICE OF SIGNAL DESIGN

DATE: 12/12/13
DES: WIT CHK: NBT
PID: 85679
WO: 22817

UNION PACIFIC RAILROAD
NORMAL, ILLINOIS
BROADWAY
JOLIET SUBDIVISION
Office of AVP Engineering - Signal Omaha, Nebraska

SH. 10D
DOT 290812D
M.P. 124.20
ID=CSL12420.10DX



NOTE: ALL DIMENSIONS SHOWN ARE APPROXIMATE.

8X10 HOUSE WITH HEATER AND BLOWER U.P. PART#520-2532

NEW SHEET

Designed: 12/12/13
TIER 4 ILLINOIS HIGH SPEED RAIL PROJECT
PHASE 3
MP 118.25-124.85
Reg#: 15: WO#: 22817 NBT / WIT/RLL

CIRCUIT MODIFICATIONS ARE NOT TO BE MADE WITHOUT AUTHORITY FROM THE OFFICE OF SIGNAL DESIGN

DATE: 12/12/13	
DES: WIT CHK: NBT	
PID: 85679	
WO: 22817	

UNION PACIFIC RAILROAD

NORMAL, ILLINOIS
BROADWAY
JOLIET SUBDIVISION

Office of AVP Engineering - Signal Omaha, Nebraska

SH.	11
DOT	290812D
M.P.	124.20
ID=CSL12420.11X	





NOTE: ALL DIMENSIONS SHOWN ARE APPROXIMATE.







NEW SHEET

Designed: 12/12/13
TIER 4 ILLINOIS HIGH SPEED RAIL PROJECT
PHASE 3
MP 118.25-124.85
Rec#: WO#: 22817
IS: / /NBT /WIT/RLL

CIRCUIT MODIFICATIONS ARE NOT TO BE MADE WITHOUT AUTHORITY FROM THE OFFICE OF SIGNAL DESIGN

DATE: 12/12/13	
DES: WIT	CHK: NBT
PID: 85679	
WO: 22817	

UNION PACIFIC RAILROAD

NORMAL, ILLINOIS
BROADWAY
JOLIET SUBDIVISION

Office of AVP Engineering - Signal Omaha, Nebraska

SH.	12
DOT	290812D
M.P.	124.20
ID=CSL12420.12X	





NOTE: ALL DIMENSIONS SHOWN ARE APPROXIMATE.

NEW SHEET

Designed: 12/12/13
TIER 4 ILLINOIS HIGH SPEED RAIL PROJECT
PHASE 3
MP 118.25-124.85
Rec#: WO#: 22817
IS: / /NBT
/WIT/RLL

CIRCUIT MODIFICATIONS ARE NOT TO BE MADE WITHOUT AUTHORITY FROM THE OFFICE OF SIGNAL DESIGN

DATE: 12/12/13	
DES: WIT	CHK: NBT
PID: 85679	
WO: 22817	

UNION PACIFIC RAILROAD

NORMAL, ILLINOIS
BROADWAY
JOLIET SUBDIVISION

Office of AVP Engineering - Signal Omaha, Nebraska

SH.	13
DOT	290812D
M.P.	124.20
ID=CSL12420.13X	





NOTE: ALL DIMENSIONS SHOWN ARE APPROXIMATE.



NEW SHEET

Designed: 12/12/13
TIER 4 ILLINOIS HIGH SPEED RAIL PROJECT
PHASE 3
MP 118.25-124.85
Rec#: WO#: 22817
IS: / /NBT
/ /WIT/RLL

CIRCUIT MODIFICATIONS ARE NOT TO BE MADE WITHOUT AUTHORITY FROM THE OFFICE OF SIGNAL DESIGN

DATE: 12/12/13	
DES: WIT CHK: NBT	
PID: 85679	
WO: 22817	

UNION PACIFIC RAILROAD

NORMAL, ILLINOIS
BROADWAY
JOLIET SUBDIVISION

Office of AVP Engineering - Signal Omaha, Nebraska

SH.	14
DOT	290812D
M.P.	124.20
ID=CSL12420.14X	

Minimum Program Steps Report

Location and SIN

DOT Number: 290812D
Milepost Number: 124.20
Site Name: NORMAL, IL

SIN: 762010010016 *

* Parameter is part of office check number calculation.

MCF and Template Selection

MCF Name: GCP-T6X-02-6.mcf
MCF Revision: 26
MCFCRC: 494D2656

Template = 1A:6 Trk Bi (OCCN) *

* Parameter is part of office check number calculation.

Minimum Program Steps

TEMPLATE: module configuration
Track 2/RIO 1 Slot = Track (OCCN) *
Track 5/RIO 2 Slot = RIO (OCCN) *
Track 6/RIO 3 Slot = RIO (OCCN) *

TEMPLATE: track 1-Bi, Island
Track 1 : GCP Frequency = 285 Hz (OCCN) *
Track 1 : Approach Distance = 2648 ft (OCCN) *
Track 1 : Prime Warning Time = 44 sec (OCCN) *
Track 1 : Prime UAX = IP (OCCN) *
Track 1 : Prime UAX Pickup = 15 sec (OCCN) *
Track 1 : GCP Transmit Level = Medium (Set in Field,TCN)
Track 1 : Isl Frequency = 13.2 kHz (OCCN) *

TEMPLATE: track 2-Bi, Island
Track 2 : GCP Frequency = 285 Hz (OCCN) *
Track 2 : Approach Distance = 2648 ft (OCCN) *
Track 2 : Prime Warning Time = 44 sec (OCCN) *
Track 2 : Prime UAX = IP (OCCN) *
Track 2 : Prime UAX Pickup = 15 sec (OCCN) *
Track 2 : GCP Transmit Level = Medium (Set in Field,TCN)
Track 2 : Isl Frequency = 15.2 kHz (OCCN) *

TEMPLATE: AND 1 XR
AND 1 Enable Used = Yes (OCCN) *

TEMPLATE: SSCC
SSCC-2 Number of GPs = 2 (OCCN) *
SSCC-2 Number of GDs = 2 (OCCN) *

TEMPLATE: OOS
OOS Control = OOS IPs (OCCN) *

TEMPLATE: OP assignment 1
OUT 1.1 = AND 1 XR (OCCN) *
OUT 1.2 = T1 Island (OCCN) *
OUT 2.1 = T2 Island (OCCN) *

```
TEMPLATE:  OP assignment 2
OUT 5.1 = T1 Prime (OCCN) *
OUT 5.2 = T2 Prime (OCCN) *
OUT 6.1 = T1 Prime (OCCN) *
OUT 6.2 = T2 Prime (OCCN) *

TEMPLATE:  IP assignment 1
IN 1.1 = AND 1 XR Enable (OCCN) *
IN 1.2 = Out Of Service IP 1 (OCCN) *
IN 2.2 = Out Of Service IP 2 (OCCN) *

TEMPLATE:  IP assignment 2
IN 5.2 = GP 1.1 (OCCN) *
IN 6.1 = T1 Prime UAX (OCCN) *
IN 6.2 = T2 Prime UAX (OCCN) *
IN 6.3 = T1 Prime UAX (OCCN) *
IN 6.4 = T2 Prime UAX (OCCN) *

TEMPLATE:  IP assignment SSCC
IN 7.1 = AND 1 XR Enable (OCCN) *
IN 8.2 = GD 2.2 (OCCN) *
IN 8.3 = GP 2.2 (OCCN) *
IN 8.4 = GD 2.1 (OCCN) *
IN 8.5 = GP 2.1 (OCCN) *

TEMPLATE:  SEAR
SP 3.1 = General 3 (OCCN) *
SP 4.1 = General 4 (OCCN) *

MS4000 configuration
Track 1 : GCP Frequency = 285 Hz (OCCN,TCN) (Hidden) *
Track 1 : Prime UAX = IP (OCCN) (Hidden) *
Track 1 : Prime UAX Pickup = 15 sec (OCCN) (Hidden) *
Track 1 : Isl Frequency = 13.2 kHz (OCCN) (Hidden) *
Track 1 : Pickup Delay (2s +) = 2 sec (OCCN) (Hidden) *
IN 1.1 = AND 1 XR Enable (OCCN) (Hidden) *
IN 1.2 = Out Of Service IP 1 (OCCN) (Hidden) *

MS4000 Predictor
Track 1 : Prime Warning Time = 44 sec (OCCN) (Hidden) *

GCP:  track 1
Track 1 : Island Distance = 201 ft (Set in Field,TCN)

GCP:  track 2
Track 2 : Island Distance = 201 ft (Set in Field,TCN)

ISLAND:  track 1
Track 1 : Pickup Delay (2s +) = 2 sec (OCCN) *

ISLAND:  track 2
Track 2 : Pickup Delay (2s +) = 2 sec (OCCN) *

ADVANCED:  site options
Daylight Savings = Off (Set in Field)

SEAR:  slot 1-4 inputs
IN 2.1 = General 2 (OCCN) *
IN 3.1 = General 1 (OCCN) *
IN 3.2 = General 3 (OCCN) *
IN 4.1 = Vehicle Det Hlth (OCCN) *
IN 4.2 = 3 Vehicle Detect (OCCN) *
```

SEAR: inputs slot 5
IN 5.3 = General 2 (OCCN) *
IN 5.4 = General 1 (OCCN) *

Express: MS4000 configuration
Track 1 : GCP Frequency = 285 Hz (OCCN,TCN) (Hidden) *
Track 1 : Prime UAX = IP (OCCN) (Hidden) *
Track 1 : Prime UAX Pickup = 15 sec (OCCN) (Hidden) *
Track 1 : Pickup Delay (2s +) = 2 sec (OCCN) (Hidden) *
IN 1.1 = AND 1 XR Enable (OCCN) (Hidden) *
IN 1.2 = Out Of Service IP 1 (OCCN) (Hidden) *

Express: MS4000 Predictor
Track 1 : Prime Warning Time = 44 sec (OCCN) (Hidden) *

* Parameter is part of office check number calculation.

Check Numbers

Office Check Number: 02122BD8
Config. Check Number: 1CBDA5B1
(Based on MCF Revision 26)

Parameters not part of office check number calculation:

Track 1 : GCP Transmit Level = Medium (Set in Field)
Track 2 : GCP Transmit Level = Medium (Set in Field)
Track 1 : Island Distance = 201 ft (Set in Field)
Track 2 : Island Distance = 201 ft (Set in Field)
Daylight Savings = Off (Set in Field)

Comments

SLOT 2 SEAR INPUTS:
IN 2.1 = GATES F & H GD
SLOT 3 SEAR INPUTS:
SP 3.1 = ITCS XHSR
IN 3.1 = GATES E & G GD
IN 3.2 = PED GATES GP
SLOT 4 SEAR INPUTS:
SP 4.1 = ITCS XHR
IN 4.1 = EGMSHR
IN 4.2 = LTOR
SLOT 5 SEAR INPUTS:
IN 5.3 = DXGR
IN 5.4 = CXGR

Configuration Package File

Filename: CSL12420_290812D.pac
Path: C:\PAC File\
Date/Time: 2/19/2015 15:33:18